

MULTIMASTER MM 700 Max Top



Oscillating MultiTools - MM 700

Our best MultiTool for ultra-rapid work progress for interior construction and renovation with 60 accessories – for sawing in wood, metal, plastics, for removing tiles, cutting silicone caulking and carpeting, and removing residual and tile adhesive.

Product number: 7 229 68 61 09 0

Details

- Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- > 450 W FEIN high-performance motor: Durable, overload-protected, high-performance motor with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > Industrial-strength cable: The 16 ft (5m) rubber-clad, industrial-quality cord gives you room to work.



Price includes

- 2 E-Cut standard saw blades, 2 E-Cut standard saw blades, curved (1-3/8 [35] in[mm]) curved (2-1/2 [65] in[mm]) 1 E-Cut Long Life saw blade (10 1 E-Cut Precision BIM saw blade 🏑 (1-3/8 [35] in[mm]) mm) 1 E-Cut Long Life saw blade (1-1 E-Cut Long Life saw blade (1-1/4 [32] in[mm]) 5/8 [42] in[mm]) 1 HM saw blade (Ø 3 [75] in[mm]) 1 segmented saw blade (Ø 3-3/8 🏑 [85] in[mm]) 1 rigid scraper blade 1 mushroom-shaped cutting blade 1 perforated sanding pad 40 perforated sanding sheets (10 🦯 1 dust extraction device each of grits 60, 80, 120, 180) 1 tool case Product feature
- Mechanical interconnection

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Power consumption	450 W	Sound pressure level LpA Measurement uncertainty of the	85 dB 3 dB
Power output	250 W	measured value KpA	
Oscillations	10,000 - 19,500 opm	Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Tool mount	StarlockMax	Peak sound value	97 dB
Tool change	QuickIN	LpCpeak Measurement uncertainty of the measured value KpCpeak	3 dB
Range	2 x 2,0°		
Cable with plug	16.4 [5] ft[m]		
Weight	3.53 [1.60] lbs[kg]		

- ✓ 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])
 - 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])
 - 1 carbide rasp (triangular)

1 Multi-knife



Application examples

