

PED33 Technical Data

MODEL: PED33 – Pedestal Sump Pump

Physical Data:

DISCHARGE SIZE	1-1/2" NPT
IMPELLER TYPE	Vortex – Thermoplastic
CABLE LENGTH	8'

Liquid Handling:

SOLIDS SIZE	3/16"
MAXIMUM LIQUID TEMP.	104°F – Intermittent
ACCEPTABLE PH RANGE	6-8

Temperature:

MAXIMUM STATOR	130°C
----------------	-------

Technical Data:

POWER CORD TYPE	SJT
-----------------	-----

MOTOR HOUSING	Steel
CASING	Thermoplastic
IMPELLER	Thermoplastic
MOTOR SHAFT	SST
HARDWARE	Steel
"O" RINGS	NBR

SEAL	LIP
UPPER BEARING	6202
LOWER BEARING	6202



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com

PED33 Electrical Data

Model: PED33 – 1/3 HP Plastic Pedestal Sump Pump

R.P.M.	1750
MOTOR TYPE	PSC
GENERAL INSULATION CLASS	B
STATOR WINDING CLASS	B
MAXIMUM STATOR TEMPERATURE	130°C
VOLTAGE TOLERANCE	±10%
MOTOR PROTECTION	Thermally Protected

HP	VOLTAGE	PHASE	SERVICE FACTOR	FULL LOAD AMPS
1/3	115	1	1.0	4.0



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com