

SEWAGE PUMPS
SWFD200 Electrical Data

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWFD200M2-20	2	60	230/1	20A	1750	16.7	K	SOW	12AWG/3C	.62	N/A	N/A	350V 35MFD±5%
SWFD200M3-20	2	60	230/3	15A	1750	11.0	L	SOW	14AWG/4C	.59	N/A	N/A	N/A
SWFD200M4-20	2	60	460/3	10A	1750	5.5	L	SOW	14AWG/4C	.59	N/A	N/A	N/A
SWFD200M5-20	2	60	208/1	20A	1750	21.0	K	SOW	12AWG/3C	.62	N/R	N/R	N/R
SWFD200M6-20	2	60	208/3	15A	1750	11.5	L	SOW	14AWG/4C	.59	N/A	N/A	N/A

MOTOR TYPE	PSC (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com