

SEWAGE PUMPS
SWFD300 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWFD300M2-20	3	60	230/1	1750	28.0	D	SOW	8AWG/4C	1.0	Continuous Coil Min Voltage: 350V Pick-up Max: 200V Drop Out Max: 75V	750uf+/-5%-220VAC	40uf+/-5%-370VAC
SWFD300M3-20	3	60	230/3	1750	16.0	D	SOW	12AWG/4C	0.7	N/A	N/A	N/A
SWFD300M4-20	3	60	460/3	1750	8.0	D	SOW	12AWG/4C	0.7	N/A	N/A	N/A
SWFD300M5-20	3	60	208/1	1750	33.5	D	SOW	8AWG/4C	1.0	Continuous Coil Min Voltage: 350V Pick-up Max: 200V Drop Out Max: 75V	750uf+/-5%-220VAC	40uf+/-5%-370VAC
SWFD300M6-20	3	60	208/3	1750	18.0	D	SOW	12AWG/4C	0.7	N/A	N/A	N/A

MOTOR TYPE	CAPACITOR START/CAPACITOR RUN (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	N/A



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com