

SEWAGE PUMPS
SWHD200 Electrical Data

MODEL	HP	HZ	VOLTS/PH	BREAKER SIZE	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
SWHD200M2-20	2	60	230/1	20A	3450	18.0	L	SOW	14AWG/3C	.58	N/A	N/A	N/A
SWHD200M3-20	2	60	230/3	10A	3450	9.0	L	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWHD200M4-20	2	60	460/3	10A	3450	4.5	L	SOW	16AWG/4C	.46	N/A	N/A	N/A
SWHD200M5-20	2	60	208/1	30A	3450	20.0	L	SOW	12AWG/3C	.66	N/A	N/A	N/A
SWHD200M6-20	2	60	208/3	15A	3450	10.4	L	SOW	16AWG/4C	.46	N/A	N/A	N/A

MOTOR TYPE	PSC (1PH), INDUCTION (3PH)
GENERAL INSULATION CLASS	B
WINDING INSULATION TEMPERATURE	130°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com