

SEWAGE PUMPS

SWS50V-10 Technical Data

Physical Data:

DISCHARGE SIZE	2" NPT Discharge
IMPELLER TYPE	9-Vane - Plastic
CABLE LENGTH	10'

Liquid Handling:

SOLIDS SIZE	2"
MAXIMUM LIQUID TEMP.	104°F – Intermittent
ACCEPTABLE PH RANGE	6-8

Temperature:

WINDING INSULATION TEMP.	130°C
--------------------------	-------

Technical Data:

POWER CORD TYPE	SJTOW 18AWG/3C
MOTOR HOUSING	Cast Iron
CASING	Cast Iron
IMPELLER	Plastic
MOTOR SHAFT	SS416
HARDWARE	SST
"O" RINGS	NBR
MECHANICAL SEALS	Single Mechanical Carbon Ceramic
UPPER BEARING	Powder metallurgy
LOWER BEARING	6201

Specifications

Model	HP	Hz	Volts/Ph	RPM	Full Load Amps	Nema Start Code	Cord Type	Cord Power Size	Cord O.D.
SWS50V-10	1/2	60	115/1	1750	9.4	P	SOW	18AWG/3C	.325-.360



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com