

SEWAGE PUMPS  
**SWS50V-10** Electrical Data

| MODEL     | HP  | HZ | VOLTS/PH | BREAKER SIZE | RPM  | FULL LOAD AMPS | NEMA START CODE | CORD TYPE | CORD SIZE | CORD O.D. | POTENTIAL RELAY | START CAPACITOR | RUN CAPACITOR |
|-----------|-----|----|----------|--------------|------|----------------|-----------------|-----------|-----------|-----------|-----------------|-----------------|---------------|
| SWS50V-10 | 1/2 | 60 | 115/1    | 20A          | 1750 | 9.4            | P               | SOW       | 18AWG/3C  | .33-.36   | N/A             | N/A             | N/A           |

|                                |                     |
|--------------------------------|---------------------|
| MOTOR TYPE                     | PSC (1PH)           |
| GENERAL INSULATION CLASS       | B                   |
| WINDING INSULATION TEMPERATURE | 130°C               |
| VOLTAGE TOLERANCE              | +10%                |
| MOTOR PROTECTION               | Thermally Protected |



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805

Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com