

GRINDER PUMPS  
**AGPR** Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	SOLID STATE RELAY	START CAPACITOR	RUN CAPACITOR	SWITCH TYPES
AGPR200M2-20	2	60	230/1	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	N/A
AGPR200M2-35	2	60	230/1	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	N/A
AGPR200W2-20	2	60	230/3	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	INTEGRAL
AGPR200W2-35	2	60	230/1	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	INTEGRAL
AGPR200WP2-20	2	60	230/1	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	PIGGY-BACK
AGPR200WP2-35	2	60	230/1	3450	15	G	SJTOW	14 AWG	.36-.37	SAMUSCO ECS225P	MARS 11068	MARS 12248	PIGGY-BACK

MOTOR TYPE	CSCR
GENERAL INSULATION CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Heat Sensors



P U M P

*Honest, Professional, Dependable*

1899 Cottage Street, Ashland, Ohio 44805  
 Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com