

SOLIDS HANDLING PUMPS

ANC500 Electrical Data

MODEL	HP	HZ	VOLTS/PH	RPM	FULL LOAD AMPS	NEMA START CODE	CORD TYPE	CORD SIZE	CORD O.D.	POTENTIAL RELAY	START CAPACITOR	RUN CAPACITOR
ANC500M2-35	5	60	230/1	1750	37.4	C	SOW	8AWG/4C	1.05	CONT. COIL VOLTAGE: 350V PICK-UP MAX. 200V DROP-OUT MAX. 75V	161-193UF-220 VAC	15uF±5%-370VAC
ANC500M3-35	5	60	230/3	1750	19.8	G	SOW	14AWG/4C	.71	N/A	N/A	N/A
ANC500M4-35	5	60	460/3	1750	9.9	G	SOW	14AWG/4C	.71	N/A	N/A	N/A
ANC500M5-35	5	60	208/1	1750	43.0	C	SOW	8AWG/4C	1.05	CONT. COIL VOLTAGE: 350V PICK-UP MAX. 200V DROP-OUT MAX. 75V	161-193UF-220 VAC	15uF±5%-370VAC
ANC500M6-35	5	60	208/3	1750	20.0	G	SOW	14AWG/4C	.71	N/A	N/A	N/A

MOTOR TYPE	CSCR (1PH), Induction (3PH)
GENERAL INSULATION CLASS	H
STATOR WINDING CLASS	H
WINDING INSULATION TEMPERATURE	180°C
VOLTAGE TOLERANCE	+10%
MOTOR PROTECTION	Thermally Protected



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
Telephone: 855 281-6830 • Fax: 877 326-1994 • ashlandpump.com